tortillaXpress pizzaXpress



Commercial Electromechanical Dual-Heat Press

Model No.

D-TXE-2-18

The D-TXE-2-18 commercial electromechanical dual-heat dough press's versatility in that it can be used with dual heat, upper heat only or no heat, makes it the perfect choice for all types of products. The D-TXE-2-18 is press for high volume production. It's heavy duty stainless steel construction and electric motor driven components make it the best semiautomatic press in the industry without the use of hydraulics or accessory air compressor. The dough press is an easy, affordable way to improve your production time, as well as your finished product. The D-TXE-2-18 is a swing away design with upper and lower heated platens.

D-TXE-2-18

Dual Heated Platens:

Pizza/Tortilla Dough

- speeds up production (faster pressing times)
- enables pressing thinner products
- · aids dough flow

· allows dough to be pressed straight from refrigeration unit

· helps keep dough from shrinking back

Pizza Dough

- aids in pressing sticky dough
- helps activate yeast for faster proofing if desired
- enables par baking pizza crust

Tortilla Dough

• initial grill off for tortillas

Pressing Tips

Tortilla Dough(Pre-Grill)

- Recommended Time:
- 1 3 seconds
- Recommended Temperature: 275° - 300°

Par Bake Pizza Dough

- Recommended Time:
- Depends on percent par bake desired
- Recommended Temperature:

225° - 300°

Fresh Pizza Dough

Recommended Time:

Warm dough, moderate to high yeast....2 seconds Cold dough, moderate yeast......4-6 seconds Cold dough, small amount of yeast......8 seconds

Recommended Temperature:

Warm dough....110°F, Cold dough...150°F

Variable Thickness Control

 makes it possible to acheive desired thickness and ensures consistent thickness at the same dough ball weight



- 18 " platen allows for making variable crust sizes and thicknesses up to 18 inches - the size of the crust is determined by the weight of the dough ball and the thickness setting.
- depends on the desired size of the crust... 9'' to 18'' = 150-200/hr. 7'' to 9'' = 300-400/hr, 6'' or under = 600-800/hr

Finished Product:

 pressed dough keeps air in the crust vs. sheeted dough where the air is forced out of the crust. Pressed dough is consistent in thickness and size vs. hand prepared where the thickness and size can be inconsistent

- presses require no skilled labor
- presses are safe and have no age requirements unlike sheeters/.rollers

Use:

• D-TXE-2-18 is easy to use...prepare dough balls, set temp/thickness, place doughball on lower platen, and press the dough. NOTE: Operation instruction, hold both start buttons in for 2 seconds to begin pressing operation.



J.D. Honigberg International, Inc. 155 N. Pfingsten Road, Suite 150 Deerfield, IL 60015 USA

Tel: 847-412-0200 • Fax: 847-412-0034

email: catering@jdhintl.com • www.jdhcatering.com

Labor:

tortillaXpress pizzaXpress



Commercial Electromechanical Dual-Heat Press

Model No. **D-TXE-2-18**

Features Include:

- · digital temperature control displays current reading
- digital timer (count down begins automatically when platen lowers and resets after the platen raises)
- full range thickness adjustment from paper thin to 7/8"
- bottom swing out design saves space and is easier to use than top swinging models
- illuminated On/Off switch
- two start buttons for hands clear operation
- heat indicating light that turns off when set temperature is reached
- flattens dough balls into pizzas up to 18" in diameter
- stainless steel exterior with aluminum upper and lower platens
- sleek, modern, durable, easy to clean design
- emergency stop button

Optional Feature:

• Non-stick Xylan coated upper and lower platens

Certifications:

- ETL
- NSF Listed
- ETL Canadian Standard

Recommended Cleaning Instructions:

• wipe down with a moist towel - if needed, use damp sponge with minimal soap & water and then dry off

DIMENSIONS

Width: 18 3/16 inches, 46.2 centimeters Height: 25 1/8 inches, 63.8 centimeters Depth: 24 11/16 inches, 62.7 centimeters

WEIGHT

Shipping: 250 lbs


ELECTRICAL


220 Volt / 60 Hz 3100 Watts 15 Amps


Standard 6-20P NEMA Plug


TEMPERATURE RANGE

OFF - 450°F, 232°C upper & lower platens











doughXpress **HIX Corporation Food Division** Product improvement may require us to change

specifications without notice. Revised January 2011

J.D. Honigberg International, Inc.

155 N. Pfingsten Road, Suite 150 Deerfield, IL 60015 USA

Tel: 847-412-0200 • Fax: 847-412-0034

email: catering@jdhintl.com • www.jdhcatering.com